

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**


**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>A61B 17/39</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 97/16127</b> <b>(43) International Publication Date:</b> 9 May 1997 (09.05.97)
<b>(21) International Application Number:</b> PCT/US96/15852 <b>(22) International Filing Date:</b> 2 October 1996 (02.10.96) <b>(30) Priority Data:</b> 08/556,784 2 November 1995 (02.11.95) US <b>(71) Applicant:</b> MEDTRONIC, INC. [US/US]; 7000 Central Avenue Northeast, Minneapolis, MN (US). <b>(72) Inventors:</b> MULIER, Peter, M., J.; 8140 Lake Elmo Avenue, Stillwater, MN 55082 (US). HOEY, Michael, F.; 5733 Pond Drive, Shoreview, MN 55126 (US). <b>(74) Agents:</b> KINGHORN, Curtis, D. et al.; Medtronic, Inc. MS301, 7000 Central Avenue Northeast, Minneapolis, MN 55432 (US).		<b>(81) Designated States:</b> AU, CA, JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i>

**(54) Title:** BALL POINT FLUID-ASSISTED ELECTROCAUTERY DEVICE**(57) Abstract**

An electrocautery device is disclosed. In accordance with one aspect of the invention, the electrocautery electrode/tip is provided with a hollow, conductive tube terminating at its distal end in a ball point type tip. Fluid, preferably conductive fluid, is applied to the proximal end of the hollow electrode/tip, and expelled from the distal end thereof during electrocautery. The ball point distal tip allows the distal tip to be directly applied to the tissue and "rolled" or slid along the tissue. This allows the distal tip to be moved across the tissue without dragging or snagging on the tissue. In addition, the conductive fluid expelled from the distal tip further lubricates the distal tip as it moves across the tissue. If conductive fluid is used, the conductive fluid emanating from the electrode/tip conducts the RF electrocautery energy away from the distal tip so that it is primarily the fluid, rather than the distal tip that actually accomplishes the cauterizing of tissue. That is, the fluid serves as a "virtual" electrocautery electrode. Since it is the fluid, rather than the distal tip that cauterizes, coagulates and ablates, no burns or perforations are made to the tissue, reducing the amount of debris at the site. Also, the flow of fluid through the electrode/tip tends to keep the distal tip clean and cool.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LJ	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

**BALL POINT FLUID-ASSISTED ELECTROCAUTERY DEVICE****FIELD OF THE INVENTION**

This invention relates generally to the field of medical instruments, and more particularly relates to an electrocautery device.

5 Various types of electrocautery devices for incising and cauterizing body tissue are known and used in the medical field. Typically, such devices include a conductive tip or needle which serves as one electrode in an electrical circuit which is completed via a grounding electrode coupled to the patient. Incision of tissue is accomplished by applying a source of electrical energy (most commonly, a radio-  
10 frequency generator) to the tip. Upon application of the tip to the tissue, a voltage gradient is created, thereby inducing current flow and related heat generation at the point of contact. With sufficiently high levels of electrical energy, the heat generated is sufficient to cut the tissue and, advantageously, to simultaneously cauterize severed blood vessels.

15 It is widely recognized in the prior art that the often substantial amount of smoke produced by electrocauterization of tissue is at least unpleasant, and in some cases distracting or even hazardous to the operator and other attending medical personnel. As a result, it has been proposed, and is common, to provide an electrocautery device with smoke-aspirating capabilities, such that the smoke  
20 produced from electrocauterization is quickly withdrawn from the area of incision. Smoke aspiration may be accomplished by providing, in the handle of the electrocautery device near the electrocautery tip/electrode, an inlet port to be coupled to a vacuum or suction source. Examples of this are described in U.S. Patent No. 4,307,720 to Weber entitled "Electrocautery Apparatus and Method and  
25 Means for Cleaning the Same;" in U.S. Patent No. 5,242,442 to Hirschfeld, entitled "Smoke Aspirating Electrosurgical Device;" and in U.S. Patent No. 5,269,781 to Hewell, entitled "Suction Assisted Electrocautery Unit."

30 It has also been recognized in the prior art that the accumulation of coagulated blood, tissue rubble, and other debris on the electrode/tip of an electrocautery device can present a problem for the operator, necessitating the

periodic cleaning of the tip, e.g., by wiping the tip over sterilized gauze or the like.

This is generally regarded as undesirable, since the need to clean the electrode/tip tends to interrupt the incision procedure and increases the risks associated with contamination of the tip or the incision, damage to the tip, injury to the operator, and the like. To address this problem, it has been proposed in the prior art to provide an electrocautery instrument in which the electrode/tip is in slidable engagement with the instrument's handle, such that when the tip is retracted into the hand, any adhering debris automatically scraped off onto the tip of the handle. Such an instrument is proposed in the above-referenced Weber, Jr. '720 patent.

While this arrangement may have some benefit, it still may be necessary to wipe off the tip of the handle once the tip is retracted. It is believed that a more direct and effective approach to the problem would be to reduce the amount of debris created during the electrocautery process, thereby eliminating or at least reducing the need to clean the electrode/tip.

Atrial fibrillation is the condition where the normal rhythmic contractions of the heart are replaced by rapid irregular twitchings of the muscular heart wall. At least 1 million people in the U.S. suffer from atrial fibrillation. There are at least three detrimental side effects that occur during atrial fibrillation: a rapid irregular heartbeat; impaired cardiac hemodynamics due to a loss of AV synchrony; and an increased vulnerability to thromboembolism. Surgical Treatment of Cardiac Arrhythmias, by Hurst, J. Willis, M.D. et al, pg. 867.

The typical treatment for atrial fibrillation has been to give the patient drugs. For most patients with atrial fibrillation, this therapy has been only moderately effective and has typically produced undesirable side effects.

In view of the problems with drug therapy to treat atrial fibrillation, it has been recognized as desirable to find a surgical treatment that would permanently cure atrial fibrillation. Cardiovascular Device Update, July 1995, pg. 1. Although radiofrequency catheter ablation (RFCA) has proven to be a safe and effective way of treating the most benign causes of supraventricular tachycardia (SVT), such as

Wolff-Parkinson-White and AV nodal re-entry tachycardia, using ablation to treat atrial fibrillation has proven to be challenging. Id.

The so called "maze" procedure has been developed to treat atrial fibrillation. In the "maze" procedure, incisions are made into the right and left atria via an open chest surgical procedure. These incisions are located to interrupt all the potential re-entry circuit patterns that could occur in the atria and cause atrial fibrillation. The clinical success with the "maze" procedure has been good.

A problem with the "maze" procedure is that it requires open chest surgery which is undesirable. It has been recognized that it would be desirable to duplicate the "maze" procedure with ablation. Id. at pg. 3. This would allow the possibility of performing a "maze"-like procedure thorascopically. However, it has also been recognized that current ablation technology has not developed to allow the "maze" procedure to be duplicated with ablation. Id.

A problem with prior art ablation has been that the ablating tip, if left in contact with a piece of tissue for too long, will burn through and perforate the tissue. In many applications, it has proven difficult to balance leaving an ablating tip in position on a piece of tissue for a sufficient time to allow the tissue to be ablated but not leave it in place for a length of time to burn through and thereby perforate the tissue.

Another problem with prior art ablation devices is that if the ablating tips are left in contact with the tissue too long, the tip "sticks" to the tissue being ablated. In removing the tip, large portions of tissue are often removed attached to the tip. This is not only a result to be avoided because of the tissue damage, but it is time consuming and irritating to the physician. These are clearly problems to be avoided.

#### **SUMMARY OF THE INVENTION**

In view of the foregoing considerations, the present invention is directed to an improved electrocautery instrument.

In accordance with one aspect of the invention, the electrocautery electrode/tip is implemented with a hollow, conductive tube terminating at its distal

end in a ball point type tip. Conductive fluid is applied to the proximal end of the hollow electrode/tip, and expelled from the distal end thereof during electrocautery. The ball point distal tip allows the distal tip to be directly applied to the tissue and "rolled" or slid along the tissue. This allows the distal tip to be moved across the tissue without dragging or snagging on the tissue. In addition, the conductive fluid expelled from the distal tip further lubricates the distal tip as it moves across the tissue.

In accordance with another aspect of the invention, the conductive fluid emanating from the electrode/tip conducts the RF electrocautery energy away from the distal tip so that it is primarily the fluid, rather than the distal tip that actually accomplishes the cauterizing of tissue. That is, the fluid serves as a "virtual" electrocautery electrode. Since it is the fluid, rather than the distal tip that cauterizes, coagulates and ablates, no burns or perforations are made to the tissue, reducing the amount of debris at the site of ablation. Also, the flow of fluid through the electrode/tip tends to keep the distal tip clean and cool.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

The foregoing and other aspects of the present invention may perhaps be best appreciated with reference to a detailed description of a specific embodiment of the invention, when read in conjunction with the accompanying drawings, wherein:

Figure 1 is a perspective view of an electrocautery instrument in accordance with one embodiment of the invention;

Figure 2 is a perspective view of the invention separated from the handle.

Figure 3 is a enlarged perspective view of the distal end of the electrocautery device of Figure 1 showing the electrode/tip.

Figure 4 is a cross-sectional view of the electrode/tip of the device of Figures 1, 2 and 3.

Figure 5 is a cross-sectional view of another embodiment of electrode/tip of the invention.

## DETAILED DESCRIPTION OF A SPECIFIC EMBODIMENT OF THE INVENTION

Referring to Figure 1, there is shown a perspective view of a fluid-assisted electrocautery device 10 in accordance with one embodiment of the invention.

5 Electrocautery device 10 comprises a handle 12 and an electrocautery electrode/tip 14. Handle 12 is preferably made of a sterilizable, rigid, and non-conductive material, such as nylon or the like. Electrode/tip 14 is attached to handle 12.

10 In accordance with one aspect of the invention, electrode/tip 14 is preferably implemented using a hollow cylindrical tube 16 with a "ball point" at its distal end, as shown in the greatly enlarged perspective and cross-sectional views of Figures 3 and 4, respectively. As can be seen, a ball 18 is retained in a cavity formed by crimping metal tube 16 around ball 18. Both ball 18 and tube 16 are preferably made of an electrically conductive metal such as stainless steel. Tube 16 is crimped both proximal and distal to ball 18 at 20 and 22, respectively.

15 Ball 18 may have any diameter but balls 18 having diameters of from about 1 to about 5 mm have been found to be particularly effective for ablating. Tube 16 must have a diameter corresponding to the diameter of ball 18 as explained herein. Consequently, tube 16 preferably has an internal diameter, particularly at its distal end, of from about 1 to about 5 mm.

20 Crimping may be accomplished by a number of techniques including but not limited to placing a series of "crimps" 24 around the periphery of tube 16 that are directed toward the interior 26 of tube 16. In addition, the distal end 28 of tube 16 is "crimped" by rounding it toward the interior 26 of tube 16. In this way, ball 18 is retained between the "crimps" 24 and the rounded distal end 28. Crimping  
25 should be done so that a portion of ball 18 extends distally beyond distal end 28.

30 Tube 16 preferably has an interior 26 diameter slightly larger than the diameter of ball 18. In any case, after crimping as described above, the portion of tube 16 surrounding ball 18 should have a slightly larger internal diameter than ball 18. This allows ball 18 to freely rotate between crimps 24 and distal end 28 and still be retained at electrode/tip 14.



An electrical insulator 30 preferably surrounds tube 16 along substantially its entire length, terminating a short distance from distal end 28. Insulator 30 prevents accidental cautery from taking place at locations other than electrode/tip 14 if tube 16 should inadvertently contact patient tissue during a procedure.

5           Two connections are made to electrocautery device 10. One terminal (e.g., positive) of a radio-frequency (RF) generator (not shown in Figure 1) is electrically coupled to electrode/tip 14 via a wire 32 attached to tube 16. Contact between ball 18 and tube 16, as will be described in more detail hereafter, provides electrical potential to ball 18.

10           A source of fluid to be expelled from electrode/tip 14 is coupled to tube 16 via a flexible input line 34. Input line 34 is preferably a tube or hose. Conductive fluid is provided under pressure through tube 16 to the electrode/tip 14. The conductive fluid is introduced to tube 16, as shown in Figure 2, through input line 34 that is connected to a fluid inlet port 36 on tube 16. Conductive fluid passes  
15           from inlet line 34 through fluid inlet port 36 into tube 16 and is communicated along the length of tube 16 to electrode/tip 14 to be expelled from the distal end thereof. This creates a so-called "virtual electrode" for performing electrocautery.

          The infusion of conductive fluid simultaneously with the application of RF energy is discussed in further detail in: U.S. patent application serial number  
20           08/113,441 entitled "Method and Apparatus for R-F Ablation," filed on August 27, 1993 in the name of Peter M.J. Mulier and Michael F. Hoey, in U.S. patent application serial number 08/303,246, entitled "Method and Apparatus for RF Ablation," filed on September 8, 1994 in the name of Peter M.J. Mulier; in U.S.  
25           patent application serial number 08/302,304 entitled "Method and Apparatus for RF Ablation," filed in the name of Peter M.J. Mulier and Michael F. Hoey on September 8, 1994 and in U.S. patent application serial number 08/393,082 entitled "Fluid Assisted Electrocautery Device", filed in the name of Peter M.J. Mulier and Michael F. Hoey on February 22, 1995. The foregoing '441, '246, '304 and '082 applications (hereinafter collectively referred to as "the RF ablation applications")

are each commonly assigned to the assignee of the present invention, and incorporated by reference herein in their respective entireties.

As described in the RF ablation patent applications, the infusion of conductive fluid into the area of application of RF energy creates a "virtual electrode," the size and shape of which can be controllably modified, and which can be rendered more or less conductive, thereby modifying the spread of RF energy. By varying such factors as the RF energy and duration, the rate of infusion of conductive liquid, and the conductivity of the infused solution, the size, shape, and intensity of the "virtual electrode" -- i.e., the intensity of thermal production in the area, can be controlled. In the case of the electrocautery device in accordance with the present invention, application of the conductive solution during the application of RF energy further assists by preventing overheating of the electrode/tip, extending the point at which burning or charring of tissue would otherwise normally occur. To enhance this effect, it is contemplated that the solution being infused may first be cooled.

Conductive solutions believed to be suitable for establishing the virtual electrode include saline, saturated saline, and Ringer's solution, among others. Regarding the source of conductive fluid, it is contemplated that a conventional pump may be coupled to input line 34. Alternatively, it is contemplated that a small, pre-pressurized canister of conductive solution may be used, such that no pump is required. In one embodiment, handle 12 may be configured to receive such a pressurized canister therein, eliminating the need for input line 34.

In addition, a dye may be mixed with the conductive fluid to make the fluid more visible during the procedure using the device 10. Examples of such a dye include, but are not limited to methylene blue.

It is desirable to provide the conductive fluid to electrode/tip 14 under pressure that is controlled. In particular, it is important not to have a flow rate that allows conductive fluid to flow excessively out of the distal end 28 of electrode/tip 14. Excessive fluid flow has been shown to spread the electrical current density

over a large area of the tissue thereby minimizing, and in some cases preventing, the ablation effect.

In use, electrical potential is applied to tube 16 from a radio-frequency (RF) generator as described above. Since tube 16 is made of an electrically conductive metal, the entire tube 16 will be at an electrical potential determined by the radio-frequency (RF) generator. Conductive fluid is supplied under pressure to the device 10 so that the conductive fluid is expelled from electrode/tip 14 around ball 18.

The user of electrocautery device 10 places electrode/tip 14 at an area to ablate and moves the electrode/tip 14 across the tissue by ball 18 contacting the tissue. Ball 18 may either roll or be slid across the tissue. The fluid expelled from the distal end 28 lubricates the tissue and facilitates the movement of ball 18 across the tissue regardless of whether ball 18 rolls or slides across the tissue.

In vitro experiments have shown the following: The larger the diameter of ball 18, the wider and deeper the ablation "track" created on the tissue; Moving the electrode/tip 14 slowly across the tissue creates deeper lesions than if electrode/tip 14 is moved quickly; and the flow rate of conductive fluid through device 10 and out of electrode/tip 14 should be adequate to wet and lubricate the surface of the tissue but should not be so high as to spread across the tissue and spread the electrical current density necessary to perform the ablation. As examples of desirable flow rates of conductive fluid through the device 10, with a radio-frequency (RF) generator at 50 Watts, a flow rate of about between 0.5 and 2 cc/minute was shown to be adequate and with a radio-frequency (RF) generator at 25 Watts, a flow rate of about between 1 and 2 cc/minute was shown to be adequate. Other flow rates in these power ranges or these or different flow rates for other power settings may also be used as will be clear with practice using the invention. The examples given above being given for the purpose of illustration and are not intended to be limiting.

The device 10 may be particularly used in connection with the so called "maze" procedure described above to ablate an area of the heart to interrupt all the

potential re-entry circuit patterns that could occur in the atria and cause atrial fibrillation. The device 10 could also be used advantageously to remove hemorrhoids or varicose veins or stop esophageal bleeding to name but a few possible uses. The device removes the risk of perforation commonly found with other types of cautery, is easy to "write" with and allows deep and wide penetration and subsequently ablation.

Because of its similarity to a ball point pen, the invention provides an electrocautery device 10 that is easy to "write" with. That is, it is easy to move the distal elected/tip 14 across the tissue to be ablated because the ball 18 rolls across the tissue. In addition, by expelling fluid from electrode/tip 14, ball 18 also slides across the tissue being ablated.

Although in the embodiment of Figure 1, wire 32 and input line 34 are depicted separately, it is contemplated that these connections to device 10 may be consolidated into a single line having a fluid-conducting lumen therein for input of conductive solution alongside an insulated electrical conductor.

Various alternate configurations of electrode/tip 14 are also contemplated. In one embodiment shown in Figure 5, ball 18 is enclosed within tube 16 at the distal end 28 of tube 16. However, instead of having crimps 24 proximal to ball 18, a block 38 is placed proximal to ball 18 within tube 16. Block 38 preferably has a central lumen 40 exiting from its proximal to its distal end to allow fluid in the interior of tube 16 to pass to ball 18 where it may be expelled from distal end 28. In all other ways, this embodiment is identical to the preferred embodiment described above.

Ball 18 may also be made of a porous, electrically conductive material. In this embodiment, the porous nature of ball 18 allows fluid to not only pass around ball 18 to be expelled from distal end 28, but also allows fluid to pass through ball 18 to be expelled.

In an alternate embodiment, ball 18 may be replaced with a non-spherical contact element such as an electrically conductive elongated plug. In this embodiment, the plug would still be retained in tube 16 at the distal end 28 of tube

16 so that fluid can pass around the plug to expelled from the distal end 28. The plug would be retained by any means described above including, but not limited to, crimps 24 and the rounded distal end 28. However, because the plug is not spherical, the plug can not roll as it is moved in contact across the tissue to be ablated. Instead, the plug will slide across the tissue. In this embodiment, the plug may also be made of an electrically conductive porous material.

Although the invention has been described in connection with using a conductive fluid to create a virtual electrode for electrode/tip 14, it is clear that many of the advantages of the invention such as the smooth flow of electrode/tip 14 will also be produced with the conductive fluid replaced with non-conducting fluid such as pure water. Therefore, it is also within the scope of the invention to include the use of a non-conducting fluid.

In addition, if desired, a suction tube may be added to the device 10 to allow smoke or excess fluid to be removed from the surgical field. Such a suction tube is described in the '082 application described above, the teachings of which have been incorporated by reference herein.

Further, tube 16 may be made of an electrically insulating material except for a portion at its distal end that comes in contact with ball 14. This portion of tube 16 that comes in contact with ball 14 should be electrically conducting. In this embodiment, wire 24 extends to this electrically conducting portion of tube 16.

From the foregoing detailed description of a specific embodiment of the invention, it should be apparent that a method and apparatus for performing fluid-assisted electrocautery of body tissue has been disclosed, wherein fluid delivered out of a hollow electrocautery electrode/tip creates a virtual electrode which incises and cauterizes the tissue.

Although a specific embodiment of the invention has been described herein, this has been done solely for the purposes of illustrating various aspects of the invention, and is not intended to be limiting with respect to the scope of the invention. It is contemplated that various substitutions, alterations, and/or modifications, including but not limited to those specifically discussed herein, may

be made to the disclosed embodiment without departing from the spirit and scope of the invention as defined in the appended claims, which follow.

**WHAT IS CLAIMED IS:**



1. A fluid-assisted electrocautery instrument, comprising a tube having a proximal and a distal end, at least a portion of the distal end of the tube being electrically conductive, the tube having a lumen at least in the portion of the tube proximal to the distal end of the tube, the lumen being connectable to a source of fluid under pressure; and, an electrically conductive ball enclosed within the tube at the distal end of the tube, the ball extending distally beyond the distal end of the tube.

2. A method of performing electrocautery, comprising the steps of:

(a) applying radio-frequency energy from a source of radio-frequency to an electrocautery site via an electrically conductive ball enclosed in the end of an electrically conductive tube connected to the source of radio-frequency; and

(b) simultaneously with step (a), infusing said electrocautery site with a conductive liquid expelled from said electrode.

1 / 2





2 / 2




FIG. 3




FIG. 4




FIG. 5

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 96/15852

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 A61B17/39

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 395 363 A (BILLINGS ET AL) 7 March 1995 see abstract; figure 1 ---	1
A,P	WO 96 07360 A (MEDTRONIC) 14 March 1996 cited in the application see abstract; figure 2 -----	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \* "A" document defining the general state of the art which is not considered to be of particular relevance
- \* "E" earlier document but published on or after the international filing date
- \* "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \* "O" document referring to an oral disclosure, use, exhibition or other means
- \* "P" document published prior to the international filing date but later than the priority date claimed

- \* "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \* "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \* "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \* "&" document member of the same patent family

Date of the actual completion of the international search

11 February 1997

Date of mailing of the international search report

19. 02. 97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+ 31-70) 340-3016

Authorized officer

Papone, F

# INTERNATIONAL SEARCH REPORT

I: national application No.

PCT/US 96/15852

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 2  
because they relate to subject matter not required to be searched by this Authority, namely:  
PCT Rule 39.1 (1v)
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

# INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 96/15852

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-5395363	07-03-95	NONE	
WO-A-9607360	14-03-96	AU-A- 3150695	27-03-96